NSN 5306-01-304-5328

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-304-5328

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:
Between 1.293 inches and 1.323 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Nas4006 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6404 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-304-5328

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0