## NSN 5306-01-304-7963

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-304-7963

## Thread Class:

3a

**Thread Direction:** 

Right-hand

### Thread Length:

Between 0.345 inches and 0.395 inches

#### Fastener Length:

Between 1.480 inches and 1.510 inches

#### Head Style:

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

### Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Grip Diameter:

Between 0.2485 inches and 0.2495 inches

### **Thread Diameter:**

0.250 inches

## Grip Length:

Between 1.115 inches and 1.135 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Titanium alloy uns r56400

## Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Nas4006 assn standard single treatment response

#### **Thread Series Designator:**

Unjf

## Specification Data:

80205-nas6404 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5306-01-304-7963

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

