Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-305-0225



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.553 inches and 0.603 inches

#### Fastener Length:

Between 3.688 inches and 3.718 inches

#### **Head Style:**

Dished hexagon

## **Head Height:**

Between 0.188 inches and 0.203 inches

## Width Between Flats:

Between 0.553 inches and 0.564 inches

## **Thread Diameter:**

0.375 inches

# Grip Length:

Between 3.115 inches and 3.135 inches

#### Features Provided:

Finished head

# Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

36.0 rockwell c grip and 40.0 rockwell c grip

## Surface Finish:

63.0 microinches grip

## Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas1306 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-305-0225

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

