NSN 5306-01-305-5912

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-305-5912

The transfer of the transfer o	Ŭ
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.750 inches and 0.829 inches	
Fastener Length:	
Between 1.328 inches and 1.375 inches	
Head Style:	
Hexagon	
Head Height:	
Between 0.265 inches and 0.297 inches	
Width Between Flats:	
Between 0.740 inches and 0.752 inches	
Hole Diameter:	
Between 0.106 inches and 0.116 inches	
Thread Diameter:	
0.500 inches	
Grip Length:	
Between 0.546 inches and 0.578 inches	
Hole Quantity:	
1	
Hole Type:	
Drilled	
Features Provided:	
Finished head	
Thready Qty Per Inch (tpi):	
20	
Min. Tensile Strength (psi):	
125000 pounds per square inch	
Hardness Rating:	
26.0 rockwell c and 32.0 rockwell c	
Hole Configuration Style:	
Hexagon flats	
Material:	
Steel comp 431	
Material Specification:	
Mil-s-18732 military specification single material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	

NSN 5306-01-305-5912

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-s-18732 spec.