
## NSN 5306-01-305-9484

Machine Bolt - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.266 inches and 0.306 inches Fastener Length: Between 0.365 inches and 0.385 inches **Head Style:** Hexagon **Head Height:** Between 0.167 inches and 0.183 inches Width Between Flats: Between 0.430 inches and 0.439 inches Hole Diameter: Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.079 inches and 0.099 inches **Hole Quantity:** 1 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c **Minimum Yield Strength:** 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** 

Ams 5731 assn standard single material response

## NSN 5306-01-305-9484

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

