## NSN 5306-01-305-9490

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-305-9490
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:
Between 0.667 inches and 0.697 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Locking Feature:
Patch threads
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400 fastener
Material Specification:
Ams4928 assn standard single material response fastener or ams4967 assn standard single material response fastener
Surface Treatment:

Aluminum fastener

## NSN 5306-01-305-9490

Shear Bolt - Page 2 of 2



## **Surface Treatment Specification:**

Nas4006 assn standard single treatment response fastener

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas6404 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0