Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-306-0099

	hread Class:
	a
	hread Direction:
	Right-hand
	hread Length:
0	0.650 inches
F	astener Length:
E	Between 0.969 inches and 1.000 inches
ł	lead Style:
F	Pan
ŀ	lead Diameter:
E	Between 0.594 inches and 0.616 inches
ł	lead Height:
E	Between 0.203 inches and 0.218 inches
L	ocking Feature:
S	Strip threads
F	First Diameter From Head:
E	Between 0.248 inches and 0.253 inches
[Distance From Largest Bearing Surface Of Head To End Of First Diameter:
C	0.350 inches
٦	hread Diameter:
C	0.312 inches
٦	hready Qty Per Inch (tpi):
2	4
E	Externally Relieved Body Diameter Quantity:
1	
N	/aterial:
I	ron alloy 660
N	Naterial Specification:
A	Ams 5737 assn standard single material response
ę	Surface Treatment:
F	Passivate
S	Surface Treatment Specification:
	Qq-p-35 federal specification single treatment response
	Thread Series Designator:
	Jnjf
	Shelf Life:
	l∕a
	Jnit Of Measure:
-	
г	Demilitarization:
	No
'	

NSN 5306-01-306-0099

Externally Relieved Body Bolt - Page 2 of 2

Fiig: A003b0

