

View Online at <https://aerobasegroup.com/nsn/5306-01-306-0101>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.479 inches and 1.519 inches

Fastener Length:

Between 7.114 inches and 7.134 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.913 inches and 0.933 inches

Width Between Flats:

Between 1.052 inches and 1.072 inches

Extended Washer Diameter:

Between 1.615 inches and 1.625 inches

Extended Washer Thickness:

Between 0.212 inches and 0.232 inches

Grip Diameter:

Between 0.9980 inches and 0.9990 inches

Thread Diameter:

1.000 inches

Grip Length:

Between 5.615 inches and 5.635 inches

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0