NSN 5306-01-306-2322

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-306-2322

View Online at https://aerobasegroup.com/nsn/5306-01-306-2322
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.881 inches and 0.931 inches
Fastener Length:
Between 2.766 inches and 2.796 inches
Head Style:
Double hexagon w/hole
Head Height:
0.530 inches
Width Between Flats:
Between 0.616 inches and 0.627 inches
Extended Washer Diameter:
Between 0.940 inches and 0.950 inches
Extended Washer Thickness:
0.098 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 1.865 inches and 1.885 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-306-2322

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0