NSN 5306-01-306-2782

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-306-2782

view Orillite at https://aerobasegroup.com/nsn/3300-01-300-2762
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.569 inches and 0.619 inches
Fastener Length:
Between 4.079 inches and 4.109 inches
Head Style:
Dished hexagon
Head Height:
Between 0.219 inches and 0.234 inches
Width Between Flats:
Between 0.679 inches and 0.690 inches
Thread Diameter:
0.437 inches
Grip Length:
Between 3.490 inches and 3.510 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 40.0 rockwell c
Surface Finish:
63.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Chromate and cadmium
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1307 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-306-2782

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0