NSN 5306-01-308-1441

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-308-1441

View Online at https://aerobasegroup.com/nsn/5306-01-308-1441
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 0.603 inches
Fastener Length:
Between 0.625 inches and 0.655 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 0.052 inches and 0.072 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
30.0 Tockwell C and 40.0 Tockwell C
Surface Finish:
Surface Finish:
Surface Finish: 63.0 microinches grip
Surface Finish: 63.0 microinches grip Material:
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment:
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response Thread Series Designator:
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response Thread Series Designator: Unjf
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1226 professional/industrial association standard
Surface Finish: 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1226 professional/industrial association standard Shelf Life:

--

NSN 5306-01-308-1441

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0