## NSN 5306-01-308-2868

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-308-2868

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.345 inches
Fastener Length:
Between 0.705 inches and 0.735 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.1900 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon longitudinal hole
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-308-2868

Shear Bolt - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas6703 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0