

View Online at <https://aerobasegroup.com/nsn/5306-01-308-4265>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.500 inches

Fastener Length:

3.625 inches

Head Style:

Hexagon

Head Height:

Between 0.250 inches and 0.280 inches

Width Between Flats:

Between 0.922 inches and 0.938 inches

Shoulder Diameter:

0.622 inches first shoulder and 0.628 inches first shoulder

Shoulder Length:

2.125 inches first shoulder

Shank Unthreaded Hole Diameter:

0.125 inches first hole and 0.187 inches first hole

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

18

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.507 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

Oval point

Material:

Steel

Material Specification:

Sae j429 gr 8 assn standard single material response

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Dod-p-16232, ty z, cl 2 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.