

View Online at <https://aerobasegroup.com/nsn/5306-01-308-4810>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.425 inches

Fastener Length:

0.8625 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.455 inches and 0.510 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 0.4275 inches and 0.4475 inches

Thready Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.6845 inches first hole

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-6049, 8740 military specification single material response or ams 6322 assn standard single material response

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.