## NSN 5306-01-308-6043

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-308-6043

View Online at https://aerobasegroup.com/nsn/5306-01-308-6043
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.298 inches and 0.348 inches
Fastener Length:
Between 0.433 inches and 0.463 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Locking Feature:
Patch threads
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Plastic polyamide locking feature
Material Specification:
Ams5731 assn standard single material response fastener or ams5737 assn standard single material response fastener
Surface Treatment:

Cadmium fastener and chromate fastener

## NSN 5306-01-308-6043

Shear Bolt - Page 2 of 2



		<b>a</b> 161 41	
Surtace	I reatment	Specification	•

Qq-p-416 ty2 cl2 federal specification single treatment response fastener

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas6303 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0