

View Online at <https://aerobasegroup.com/nsn/5306-01-309-0884>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 2.401 inches and 2.431 inches

Fastener Length:

Between 2.339 inches and 2.369 inches

Head Style:

Dished hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.052 inches and 1.065 inches

Grip Diameter:

Between 0.7636 inches and 0.7646 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Grip Length:

Between 1.740 inches and 1.760 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.107 inches first hole and 2.157 inches first hole

Special Features:

Oversize shank for repair work only

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6212 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0