
NSN 5306-01-309-5438

Machine Bolt - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.784 inches and 0.814 inches Fastener Length: Between 0.828 inches and 0.875 inches **Head Style:** Hexagon **Head Height:** Between 0.178 inches and 0.198 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.190 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Hexagon corners Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unjf

3

NSN 5306-01-309-5438

Machine Bolt - Page 2 of 2



Specification Data:

80205-nas563 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0