NSN 5306-01-309-6511

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-309-6511

Thread Direction: Right-hand Thread Length: Between 13.50 millimeters and 14.50 millimeters Fastener Length: Between 18.75 millimeters and 19.25 millimeters Head Style: Hexagon **Head Height:** Between 4.26 millimeters and 4.56 millimeters Width Between Flats: Between 9.78 millimeters and 10.00 millimeters **Grip Diameter:** Between 5.988 millimeters and 6.000 millimeters **Thread Diameter:** 6.0 millimeters Grip Length: Between 4.75 millimeters and 5.25 millimeters Min. Tensile Strength (psi): 1100 megapascals **Thread Pitch In Millimeters:** 1.0 **External Thread Tolerance Class:** 4h Surface Finish: 0.8 micrometers grip **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Μ Shelf Life: N/a Unit Of Measure: ---

NSN 5306-01-309-6511

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

