## NSN 5306-01-309-6511



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-309-6511 **Thread Direction:** Right-hand Thread Length: Between 13.50 millimeters and 14.50 millimeters Fastener Length: Between 18.75 millimeters and 19.25 millimeters **Head Style:** Hexagon **Head Height:** Between 4.26 millimeters and 4.56 millimeters Width Between Flats: Between 9.78 millimeters and 10.00 millimeters **Grip Diameter:** Between 5.988 millimeters and 6.000 millimeters **Thread Diameter:** 6.0 millimeters **Grip Length:** Between 4.75 millimeters and 5.25 millimeters Min. Tensile Strength (psi): 1100 megapascals **Thread Pitch In Millimeters:** 1.0 **External Thread Tolerance Class:** 4h **Surface Finish:** 0.8 micrometers grip **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

М

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5306-01-309-6511

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0