NSN 5306-01-309-6512

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-309-6512

Thread Direction: Right-hand Thread Length: Between 33.50 millimeters and 34.50 millimeters Fastener Length: Between 78.75 millimeters and 79.25 millimeters Head Style: Hexagon **Head Height:** Between 13.19 millimeters and 13.63 millimeters Width Between Flats: Between 29.67 millimeters and 30.00 millimeters **Grip Diameter:** Between 19.979 millimeters and 20.000 millimeters **Thread Diameter:** 20.0 millimeters Grip Length: Between 44.75 millimeters and 45.25 millimeters Min. Tensile Strength (psi): 1100 megapascals **Thread Pitch In Millimeters:** 1.5 **External Thread Tolerance Class:** 4h Surface Finish: 0.8 micrometers grip **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Μ Shelf Life: N/a Unit Of Measure:

--

NSN 5306-01-309-6512

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

