## NSN 5306-01-309-7040

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-309-7040

Thread Directions
Thread Direction:
Right-hand
Thread Length:
Between 21.50 millimeters and 22.50 millimeters
Fastener Length:
Between 76.75 millimeters and 77.25 millimeters
Head Style:
Hexagon
Head Height:
Between 7.23 millimeters and 7.59 millimeters
Width Between Flats:
Between 16.73 millimeters and 17.00 millimeters
Grip Diameter:
Between 9.985 millimeters and 10.000 millimeters
Thread Diameter:
10.0 millimeters
Grip Length:
Between 54.75 millimeters and 55.25 millimeters
Min. Tensile Strength (psi):
1100 megapascals
Thread Pitch In Millimeters:
1.5
External Thread Tolerance Class:
4h
Surface Finish:
0.8 micrometers grip
Product Name:
Navy special project
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
M
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-309-7040

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0