## NSN 5306-01-309-7042

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-309-7042 **Thread Direction:** Right-hand Thread Length: Between 23.50 millimeters and 24.50 millimeters Fastener Length: Between 143.75 millimeters and 144.25 millimeters **Head Style:** Hexagon **Head Height:** Between 8.23 millimeters and 8.59 millimeters Width Between Flats: Between 18.67 millimeters and 19.00 millimeters **Grip Diameter:** Between 11.982 millimeters and 12.000 millimeters **Thread Diameter:** 12.0 millimeters **Grip Length:** Between 119.75 millimeters and 120.25 millimeters Min. Tensile Strength (psi): 1100 megapascals **Thread Pitch In Millimeters:** 1.5 **External Thread Tolerance Class:** 4h **Surface Finish:** 0.8 micrometers grip **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Μ Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5306-01-309-7042

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0