

View Online at <https://aerobasegroup.com/nsn/5306-01-309-7057>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.629 inches and 0.665 inches

Fastener Length:

Between 3.583 inches and 3.603 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.251 inches and 0.266 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4982 inches and 0.4991 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.500 inches

Grip Length:

Between 2.938 inches and 2.954 inches

Features Provided:

Retaining clip

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 41.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.483 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 4130 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0