NSN 5306-01-309-8543

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-309-8543

| Thread Discrete. |
|--|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 33.75 millimeters and 34.25 millimeters |
| Fastener Length: |
| Between 163.75 millimeters and 164.25 millimeters |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 12.78 millimeters and 13.22 millimeters |
| Width Between Flats: |
| Between 29.67 millimeters and 30.00 millimeters |
| Grip Diameter: |
| Between 19.979 millimeters and 20.000 millimeters |
| Thread Diameter: |
| 20.0 millimeters |
| Grip Length: |
| Between 129.75 millimeters and 130.25 millimeters |
| Min. Tensile Strength (psi): |
| 1100 megapascals |
| Thread Pitch In Millimeters: |
| 1.5 |
| External Thread Tolerance Class: |
| 4h |
| Surface Finish: |
| 3.2 micrometers threads |
| Product Name: |
| Navy special project |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5735 assn standard single material response or ams 5732 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| M |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5306-01-309-8543

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0