## NSN 5306-01-309-8543

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-309-8543

| Thread Discrete.   |
|--|
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 33.75 millimeters and 34.25 millimeters  |
| Fastener Length:   |
| Between 163.75 millimeters and 164.25 millimeters  |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 12.78 millimeters and 13.22 millimeters  |
| Width Between Flats:   |
| Between 29.67 millimeters and 30.00 millimeters  |
| Grip Diameter:   |
| Between 19.979 millimeters and 20.000 millimeters  |
| Thread Diameter:   |
| 20.0 millimeters   |
| Grip Length:   |
| Between 129.75 millimeters and 130.25 millimeters  |
| Min. Tensile Strength (psi):   |
| 1100 megapascals   |
| Thread Pitch In Millimeters:   |
| 1.5  |
| External Thread Tolerance Class:   |
| 4h   |
| Surface Finish:  |
| 3.2 micrometers threads  |
| Product Name:  |
| Navy special project   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams 5735 assn standard single material response or ams 5732 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| M  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

## NSN 5306-01-309-8543

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0