

View Online at <https://aerobasegroup.com/nsn/5306-01-309-8805>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.551 inches

**Fastener Length:**

Between 1.036 inches and 1.066 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.348 inches

**Width Between Flats:**

0.372 inches

**Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

**Extended Washer Thickness:**

0.082 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

0.343 inches

**End Application:**

F-15 aircraft pdm

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Special Features:**

1/32 in. Oversize (salvage) part for mb84

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.