

View Online at <https://aerobasegroup.com/nsn/5306-01-309-8805>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.551 inches

Fastener Length:

Between 1.036 inches and 1.066 inches

Head Style:

Double hexagon w/hole

Head Height:

0.348 inches

Width Between Flats:

0.372 inches

Extended Washer Diameter:

Between 0.521 inches and 0.531 inches

Extended Washer Thickness:

0.082 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

0.343 inches

End Application:

F-15 aircraft pdm

Thread Diameter:

0.312 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Double hexagon longitudinal hole

Special Features:

1/32 in. Oversize (salvage) part for mb84

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.