

View Online at <https://aerobasegroup.com/nsn/5306-01-309-9902>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.425 inches

Fastener Length:

Between 1.410 inches and 1.440 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 0.990 inches and 1.010 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Criticality Code Justification:

Feat

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.247 inches first hole

Surface Finish:

63.0 microinches grip

Special Features:

Safety critical item. Apply one coat of mil-p-23377, type 1, cl 1 or 3 and two top coats of mil-c-46168, color code 33538 per fed-std-595 to top of head

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.