

View Online at <https://aerobasegroup.com/nsn/5306-01-311-4063>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.937 inches

Fastener Length:

Between 4.860 inches and 4.890 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.988 inches and 1.000 inches

Head Height:

0.595 inches

Hole Diameter:

Between 0.070 inches and 0.075 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

Between 0.563 inches and 0.566 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel comp e4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8503 military specification 3rd material response

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas150 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.