NSN 5306-01-311-9903

Machine Bolt - Page 1 of 2

Between 0.300 inches and 0.320 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-311-9903

Between 0.300 inches and 0.320 inches Head Style: Double hexagon w/hole Head Height: Between 0.320 inches and 0.340 inches Width Between Flats: 0.308 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Double hexagon w/hole Head Height: Between 0.320 inches and 0.340 inches Width Between Flats: 0.308 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.070 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Head Height: Between 0.320 inches and 0.340 inches Width Between Flats: 0.308 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Between 0.320 inches and 0.340 inches Width Between Flats: 0.308 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Width Between Flats: 0.308 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
0.308 inches Extended Washer Diameter: 0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Extended Washer Diameter: 0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
0.438 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Between 0.060 inches and 0.070 inches Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Hole Diameter: Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Hole Type: Drilled Thready Qty Per Inch (tpi):
Drilled Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
28
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Special Features:
Make from ms9147-06
Material:
Steel
Material Specification:
Ams6322-80 assn standard single material response
Surface Treatment:
Cadmium

NSN 5306-01-311-9903

Machine Bolt - Page 2 of 2



Surface Treatment Speci

Qq-p-416, type 1, class 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0