## NSN 5306-01-311-9903

Machine Bolt - Page 1 of 2

Between 0.300 inches and 0.320 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-311-9903

Between 0.300 inches and 0.320 inches  Head Style:  Double hexagon w/hole  Head Height:  Between 0.320 inches and 0.340 inches  Width Between Flats: 0.308 inches  Extended Washer Diameter: 0.438 inches  Extended Washer Thickness:  Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application:  Lower bearing, c5a/b  Thread Diameter: 0.250 inches  Hole Quantity: 2  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
Double hexagon w/hole  Head Height:  Between 0.320 inches and 0.340 inches  Width Between Flats:  0.308 inches  Extended Washer Diameter:  0.438 inches  Extended Washer Thickness:  Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.070 inches  End Application:  Lower bearing, c5a/b  Thread Diameter:  0.250 inches  Hole Quantity:  2  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
Head Height:  Between 0.320 inches and 0.340 inches  Width Between Flats: 0.308 inches  Extended Washer Diameter: 0.438 inches  Extended Washer Thickness: Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application: Lower bearing, c5a/b  Thread Diameter: 0.250 inches  Hole Quantity: 2  Hole Type: Drilled  Thready Qty Per Inch (tpi):
Between 0.320 inches and 0.340 inches  Width Between Flats: 0.308 inches  Extended Washer Diameter: 0.438 inches  Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter:  Between 0.045 inches and 0.049 inches End Application: Lower bearing, c5a/b  Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Width Between Flats:  0.308 inches  Extended Washer Diameter: 0.438 inches  Extended Washer Thickness:  Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application:  Lower bearing, c5a/b  Thread Diameter:  0.250 inches  Hole Quantity: 2  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
0.308 inches  Extended Washer Diameter: 0.438 inches  Extended Washer Thickness: Between 0.060 inches and 0.070 inches  Hole Diameter: Between 0.045 inches and 0.049 inches  End Application: Lower bearing, c5a/b  Thread Diameter: 0.250 inches Hole Quantity: 2  Hole Type: Drilled Thready Qty Per Inch (tpi):
Extended Washer Diameter:  0.438 inches  Extended Washer Thickness:  Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application:  Lower bearing, c5a/b  Thread Diameter:  0.250 inches  Hole Quantity:  2  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
0.438 inches  Extended Washer Thickness:  Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application:  Lower bearing, c5a/b  Thread Diameter:  0.250 inches  Hole Quantity:  2  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
Extended Washer Thickness:  Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application:  Lower bearing, c5a/b  Thread Diameter:  0.250 inches  Hole Quantity:  2  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
Between 0.060 inches and 0.070 inches  Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application:  Lower bearing, c5a/b  Thread Diameter:  0.250 inches  Hole Quantity:  2  Hole Type:  Drilled  Thready Qty Per Inch (tpi):
Hole Diameter:  Between 0.045 inches and 0.049 inches  End Application: Lower bearing, c5a/b  Thread Diameter:  0.250 inches  Hole Quantity: 2  Hole Type: Drilled  Thready Qty Per Inch (tpi):
Between 0.045 inches and 0.049 inches  End Application: Lower bearing, c5a/b  Thread Diameter: 0.250 inches  Hole Quantity: 2  Hole Type: Drilled  Thready Qty Per Inch (tpi):
End Application: Lower bearing, c5a/b Thread Diameter: 0.250 inches Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Lower bearing, c5a/b  Thread Diameter: 0.250 inches  Hole Quantity: 2  Hole Type: Drilled  Thready Qty Per Inch (tpi):
Thread Diameter:  0.250 inches  Hole Quantity: 2  Hole Type: Drilled Thready Qty Per Inch (tpi):
0.250 inches  Hole Quantity: 2  Hole Type: Drilled Thready Qty Per Inch (tpi):
Hole Quantity: 2 Hole Type: Drilled Thready Qty Per Inch (tpi):
2 Hole Type: Drilled Thready Qty Per Inch (tpi):
Hole Type:  Drilled  Thready Qty Per Inch (tpi):
Drilled Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
28
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Special Features:
Make from ms9147-06
Material:
Steel
Material Specification:
Ams6322-80 assn standard single material response
Surface Treatment:
Cadmium

## NSN 5306-01-311-9903

Machine Bolt - Page 2 of 2



Surface Treatment Speci
-------------------------

Qq-p-416, type 1, class 2 federal specification single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0