## NSN 5306-01-313-1745

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-1745

View Online at https://aerobasegroup.com/nsn/5306-01-313-1745						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.445 inches and 0.495 inches						
Fastener Length:						
Between 2.017 inches and 2.047 inches						
Head Style:						
Spline extended washer						
Head Height:						
Between 0.240 inches and 0.260 inches						
Extended Washer Diameter:						
Between 0.460 inches and 0.470 inches						
Extended Washer Thickness:						
Between 0.026 inches and 0.046 inches						
Grip Diameter:						
Between 0.2485 inches and 0.2495 inches						
Head Minor Diameter:						
Between 0.235 inches and 0.250 inches						
Thread Diameter:						
0.250 inches						
Grip Length:						
Between 1.552 inches and 1.572 inches						
Thready Qty Per Inch (tpi):						
28						
Min. Tensile Strength (psi):						
180000 pounds per square inch						
Hardness Rating:						
39.0 rockwell c and 43.0 rockwell c						
Surface Finish:						
32.0 microinches grip						
Material:						
Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-416 type 2 cl3 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Shelf Life:						

N/a

## NSN 5306-01-313-1745

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0