NSN 5306-01-313-1747

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-1747 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.445 inches and 0.495 inches **Fastener Length:** Between 3.017 inches and 3.047 inches **Head Style:** Spline extended washer **Head Height:** Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.046 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Head Minor Diameter:** Between 0.235 inches and 0.250 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 2.552 inches and 2.572 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-416 type 2 cl3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-313-1747

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0