NSN 5306-01-313-1759

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-1759	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.460 inches and 0.485 inches	
Fastener Length:	
Between 3.282 inches and 3.297 inches	
Head Style:	
Spline extended washer	
Head Height:	
Between 0.240 inches and 0.260 inches	
Extended Washer Diameter:	
Between 0.460 inches and 0.470 inches	
Extended Washer Thickness:	
Between 0.026 inches and 0.046 inches	
Grip Diameter:	
Between 0.2485 inches and 0.2495 inches	
Head Minor Diameter:	
Between 0.235 inches and 0.250 inches	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 2.812 inches and 2.822 inches	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
180000 pounds per square inch	
Hardness Rating:	
39.0 rockwell c and 43.0 rockwell c	
Surface Finish:	
32.0 microinches grip	
Material:	
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, ty2 cl3 federal specification single treatment response	
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	

N/a

NSN 5306-01-313-1759

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0