## NSN 5306-01-313-3550

Shear Bolt - Page 1 of 2

Between 0.803 inches and 0.823 inches

Between 1.428 inches and 1.448 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

Double hexagon w/hole

**Head Style:** 

За



View Online at https://aerobasegroup.com/nsn/5306-01-313-3550

Head Height:
Between 0.494 inches and 0.514 inches
Width Between Flats:
0.637 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
Between 0.113 inches and 0.133 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
0.625 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams6487 assn standard single material response
Surface Treatment:
Nickel and cadmium and chromate
Surface Treatment Specification:
Ams2416 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1785 professional/industrial association standard
Shelf Life:
N/a

## NSN 5306-01-313-3550

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0