NSN 5306-01-313-9054

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-313-9054

| Tilleau Glass. | |
|---|-------------------------|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 1.053 inches and 1.103 inches | |
| Fastener Length: | |
| Between 3.813 inches and 3.843 inches | |
| Head Style: | |
| Spline extended washer | |
| Head Height: | |
| Between 0.590 inches and 0.610 inches | |
| Extended Washer Diameter: | |
| Between 1.384 inches and 1.394 inches | |
| Extended Washer Thickness: | |
| Between 0.098 inches and 0.118 inches | |
| Grip Diameter: | |
| Between 0.7480 inches and 0.7490 inches | |
| Head Minor Diameter: | |
| Between 0.797 inches and 0.812 inches | |
| Thread Diameter: | |
| 0.750 inches | |
| Grip Length: | |
| Between 2.740 inches and 2.760 inches | |
| Thready Qty Per Inch (tpi): | |
| 16 | |
| Min. Tensile Strength (psi): | |
| 180000 pounds per square inch | |
| Hardness Rating: | |
| 39.0 rockwell c and 43.0 rockwell c | |
| Surface Finish: | |
| 32.0 microinches grip | |
| Material: | |
| Steel comp 4140 or steel comp e4340 or steel comp | 8740 or steel comp 6150 |
| Surface Treatment: | |
| Cadmium and chromate | |
| Surface Treatment Specification: | |
| Qq-p-416 type 2, cl 3 federal specification single trea | atment response |
| Thread Series Designator: | |
| Unjf | |
| Shelf Life: | |
| N/a | |
| | |

NSN 5306-01-313-9054

Shear Bolt - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A003b0