NSN 5306-01-313-9114

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9114						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.900 inches and 0.950 inches						
Fastener Length:						
Between 3.160 inches and 3.190 inches						
Head Style:						
Spline extended washer						
Head Height:						
Between 0.552 inches and 0.572 inches						
Extended Washer Diameter:						
Between 1.153 inches and 1.163 inches						
Extended Washer Thickness:						
Between 0.080 inches and 0.100 inches						
Grip Diameter:						
Between 0.6230 inches and 0.6240 inches						
Head Minor Diameter:						
Between 0.673 inches and 0.688 inches						
Thread Diameter:						
0.625 inches						
Grip Length:						
Between 2.240 inches and 2.260 inches						
Thready Qty Per Inch (tpi):						
18						
Min. Tensile Strength (psi):						
180000 pounds per square inch						
Hardness Rating:						
39.0 rockwell c and 43.0 rockwell c						
Surface Finish:						
32.0 microinches grip						
Material:						
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416 type 2, cl 3 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Shelf Life:						

N/a

NSN 5306-01-313-9114

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0