NSN 5306-01-313-9120

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-313-9120

За **Thread Direction:** Right-hand Thread Length: Between 0.900 inches and 0.950 inches **Fastener Length:** Between 6.035 inches and 6.065 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Head Minor Diameter:** Between 0.673 inches and 0.688 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 5.115 inches and 5.135 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:**

Unjf

NSN 5306-01-313-9120

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0