## NSN 5306-01-313-9122

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9122

View Online at https://aerobasegroup.com/nsn/5306-01-313-9122
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.053 inches and 1.103 inches
Fastener Length:
Between 4.813 inches and 4.843 inches
Head Style:
Spline extended washer
Head Height:
Between 0.590 inches and 0.610 inches
Extended Washer Diameter:
Between 1.384 inches and 1.394 inches
Extended Washer Thickness:
Between 0.098 inches and 0.118 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Head Minor Diameter:
Between 0.797 inches and 0.812 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 3.740 inches and 3.760 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

N/a

## NSN 5306-01-313-9122

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0