

View Online at <https://aerobasegroup.com/nsn/5306-01-313-9145>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.433 inches and 1.483 inches

**Fastener Length:**

Between 3.568 inches and 3.598 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.562 inches and 0.577 inches

**Width Between Flats:**

Between 1.614 inches and 1.627 inches

**Grip Diameter:**

Between 1.1225 inches and 1.1240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Thread Diameter:**

1.125 inches

**Grip Length:**

Between 2.115 inches and 2.135 inches

**Thread Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.226 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6618 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.