# NSN 5306-01-313-9168

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-313-9168



# **Thread Class:**

3a

**Thread Direction:** 

Right-hand

# Thread Length:

Between 0.837 inches and 0.887 inches

#### Fastener Length:

Between 2.285 inches and 2.315 inches

#### Head Style:

Spline extended washer

## Head Height:

Between 0.495 inches and 0.515 inches

## **Extended Washer Diameter:**

Between 1.037 inches and 1.047 inches

## **Extended Washer Thickness:**

Between 0.071 inches and 0.091 inches

#### **Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

#### Head Minor Diameter:

Between 0.610 inches and 0.625 inches

# Thread Diameter:

0.562 inches

Grip Length:

Between 1.428 inches and 1.448 inches

## Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

## Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

#### Surface Finish:

32.0 microinches grip

#### Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

## Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5306-01-313-9168

Shear Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

