## NSN 5306-01-313-9170

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9170 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.837 inches and 0.887 inches **Fastener Length:** Between 4.409 inches and 4.439 inches **Head Style:** Spline extended washer **Head Height:** Between 0.495 inches and 0.515 inches **Extended Washer Diameter:** Between 1.037 inches and 1.047 inches **Extended Washer Thickness:** Between 0.071 inches and 0.091 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Head Minor Diameter:** Between 0.610 inches and 0.625 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 3.552 inches and 3.572 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl3 federal specification single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-01-313-9170

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0