NSN 5306-01-313-9178

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9178 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.213 inches and 1.263 inches **Fastener Length:** Between 4.785 inches and 4.815 inches **Head Style:** Spline extended washer **Head Height:** Between 0.690 inches and 0.710 inches **Extended Washer Diameter:** Between 1.615 inches and 1.625 inches **Extended Washer Thickness:** Between 0.116 inches and 0.136 inches **Grip Diameter:** Between 0.8730 inches and 0.8740 inches **Head Minor Diameter:** Between 0.923 inches and 0.938 inches **Thread Diameter:** 0.875 inches **Grip Length:** Between 3.552 inches and 3.572 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-313-9178

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0