NSN 5306-01-313-9183

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9183

View Online at https://aerobasegroup.com/nsn/5306-01-313-9183							
Thread Class:							
3a							
Thread Direction:							
Right-hand							
Thread Length:							
Between 0.837 inches and 0.887 inches							
Fastener Length:							
Between 1.909 inches and 1.939 inches							
Head Style:							
Spline extended washer							
Head Height:							
Between 0.495 inches and 0.515 inches							
Extended Washer Diameter:							
Between 1.037 inches and 1.047 inches							
Extended Washer Thickness:							
Between 0.071 inches and 0.091 inches							
Grip Diameter:							
Between 0.5605 inches and 0.5615 inches							
Head Minor Diameter:							
Between 0.610 inches and 0.625 inches							
Thread Diameter:							
0.562 inches							
Grip Length:							
Between 1.052 inches and 1.072 inches							
Thready Qty Per Inch (tpi):							
18							
Min. Tensile Strength (psi):							
180000 pounds per square inch							
Hardness Rating:							
39.0 rockwell c and 43.0 rockwell c							
Surface Finish:							
32.0 microinches grip							
Material:							
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150							
Surface Treatment:							
Cadmium and chromate							
Surface Treatment Specification:							
Qq-p-416 ty2 cl3 federal specification single treatment response							
Thread Series Designator:							
Unjf							
Shelf Life:							
N/a							

N/a

NSN 5306-01-313-9183

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0