## NSN 5306-01-313-9198

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9198

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.900 inches and 0.950 inches
Fastener Length:
Between 3.035 inches and 3.065 inches
Head Style:
Spline extended washer
Head Height:
Between 0.552 inches and 0.572 inches
Extended Washer Diameter:
Between 1.153 inches and 1.163 inches
Extended Washer Thickness:
Between 0.080 inches and 0.100 inches
Grip Diameter:
Between 0.6230 inches and 0.6240 inches
Head Minor Diameter:
Between 0.673 inches and 0.688 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 2.115 inches and 2.135 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5306-01-313-9198

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0