NSN 5306-01-313-9200

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9200 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.053 inches and 1.103 inches **Fastener Length:** Between 2.688 inches and 2.718 inches **Head Style:** Spline extended washer **Head Height:** Between 0.590 inches and 0.610 inches **Extended Washer Diameter:** Between 1.384 inches and 1.394 inches **Extended Washer Thickness:** Between 0.098 inches and 0.118 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches **Head Minor Diameter:** Between 0.797 inches and 0.812 inches **Thread Diameter:** 0.750 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 3 federal specification single treatment response

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5306-01-313-9200

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0