## NSN 5306-01-313-9205

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9205						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.837 inches and 0.887 inches						
Fastener Length:						
Between 4.159 inches and 4.189 inches						
Head Style:						
Spline extended washer						
Head Height:						
Between 0.495 inches and 0.515 inches						
Extended Washer Diameter:						
Between 1.037 inches and 1.047 inches						
Extended Washer Thickness:						
Between 0.071 inches and 0.091 inches						
Grip Diameter:						
Between 0.5605 inches and 0.5615 inches						
Head Minor Diameter:						
Between 0.610 inches and 0.625 inches						
Thread Diameter:						
0.562 inches						
Grip Length:						
Between 3.302 inches and 3.322 inches						
Thready Qty Per Inch (tpi):						
18						
Min. Tensile Strength (psi):						
180000 pounds per square inch						
Hardness Rating:						
39.0 rockwell c and 43.0 rockwell c						
Surface Finish:						
32.0 microinches grip						
Material:						
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416 ty2 cl3 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Shelf Life:						
N/a						

N/a

## NSN 5306-01-313-9205

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0