## NSN 5306-01-313-9320

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-313-9320 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.538 inches and 0.588 inches **Fastener Length:** Between 3.673 inches and 3.703 inches **Head Style:** Bevel-conical **Head Diameter:** Between 0.521 inches and 0.531 inches **Head Height:** 0.312 inches **Hole Diameter:** Between 0.055 inches and 0.060 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.219 inches and 0.221 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c **Hole Configuration Style:** Round internal hexagon **Surface Finish:** 63.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416 type 2, cl 2 federal specification single treatment response

## NSN 5306-01-313-9320

Internal Wrenching Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A003b0