NSN 5306-01-314-4912

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-314-4912
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.433 inches and 1.483 inches
Fastener Length:
Between 3.381 inches and 3.411 inches
Head Style:
Dished hexagon
Head Height:
Between 0.562 inches and 0.577 inches
Width Between Flats:
Between 1.614 inches and 1.627 inches
Grip Diameter:
Between 1.1225 inches and 1.1240 inches
Thread Diameter:
1.125 inches
Grip Length:
Between 1.928 inches and 1.948 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
63.0 microinches grip
Product Name:
Navy special project
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1318 professional/industrial association standard
Shelf Life:

N/a

NSN 5306-01-314-4912

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0