Externally Relieved Body Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-315-2335



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.319 inches and 0.423 inches
Fastener Length:
Between 0.428 inches and 0.448 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.293 inches and 0.313 inches
Width Between Flats:
0.3125 inches
Extended Washer Diameter:
Between 0.428 inches and 0.448 inches
Extended Washer Thickness:
0.060 inches
First Diameter From Head:
Between 0.222 inches and 0.232 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.025 inches and 0.099 inches
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Externally Relieved Body Diameter Quantity:
1
Special Features:
Treat per pwa 36545-3 cagec 77445 bearing surface of head, point and grip
Material:
Nickel alloy
Material Specification:
Pwa 96 cagec 77445 mfr ref single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5306-01-315-2335

Externally Relieved Body Bolt - Page 2 of 2

Fiig: A003b0

